



The EXTRUDINGSKILL Round-Belts are made of polyurethane and are characterized by high flexibility; they can be used as a transport and transmissions belts, for example in the presence of roller conveyors. Thanks to their elasticity, the round belts can be installed on conveyors without tensioner, this allows for machines with compact design. The Round-Belts show high chemical resistance and hydrolysis resistance is higher than the polyurethanes existing standards on the market. The round straps EXTRUDINGSKILL are resistant to oils and fats.

Material: **PU FDA/EC**
Hardness: **SH 75 A**
Colour: **BLUE**
Tolerance: **+/- 3 SHA**



CODE	DIAMETER Ø		CROSS SECTION	APPROX WEIGHT	STANDARD ROLL		RECOMMENDED MIN. PULLEY Ø		FMAX/BELT (STANDARD)	
	MM	INCH			CM ²	KG/100M	M	FT	MM	INCH
120115000142	2,0	5/64	0,032	0,5	100	328	10	0,4	0,8	1,8
120115000242	3,0	1/8	0,071	0,9	100	328	20	0,8	1,8	4,0
120115000542	4,0	5/32	0,126	1,6	100	328	30	1,2	3,0	6,6
120115000742	4,8	3/16	0,181	2,2	100	328	35	1,4	4,4	9,7
120115000842	5,0	1/5	0,197	2,4	100	328	40	1,6	4,8	10,6
120115001142	6,0	7/32	0,283	3,4	100	328	50	2,0	6,8	15,0
120115001242	6,3	1/4	0,310	3,8	100	328	55	2,2	7,4	16,3
120115001442	7,0	9/32	0,385	4,7	50	164	60	2,4	9,2	20,2
120115001542	8,0	5/16	0,500	6,0	50	164	65	2,6	12,0	26,4
120115001642	9,5	3/8	0,710	8,5	50	164	75	3,0	17,0	37,4
120115001742	10,0	7/16	0,785	9,4	50	164	80	3,2	18,8	41,4
120115001842	12,0	15/32	1,130	13,5	50	164	90	3,5	27,2	59,8
120115001942	12,5	1/2	1,230	14,8	50	164	100	3,9	29,6	65,1
120115002342	15,0	19/32	1,770	21,5	50	164	120	4,7	42,4	93,3