



The EXTRUDINGSKILL Round-Belts are made of polyurethane and are characterized by high flexibility; they can be used as a transport and transmissions belts, for example in the presence of roller conveyors. Thanks to their elasticity, the round belts can be installed on conveyors without tensioner, this allows for machines with compact design. The Round-Belts show high chemical resistance and hydrolysis resistance is higher than the polyurethanes existing standards on the market. The round straps EXTRUDINGSKILL are resistant to oils and fats.

Material: **PU FDA/EC**
Hardness: **SH 85 A**
Colour: **TRANSPARENT**
Tolerance: **+/- 3 SHA**



CODE	DIAMETER Ø		CROSS SECTION	APPROX WEIGHT	STANDARD ROLL		RECOMMENDED MIN. PULLEY Ø		FMAX/BELT (STANDARD)	
	MM	INCH			CM ²	KG/100M	M	FT	MM	INCH
120115000174	2,0	5/64	0,032	0,5	100	328	15	0,6	1,1	2,4
120115000274	3,0	1/8	0,071	0,9	100	328	25	1,0	2,1	4,6
120115000574	4,0	5/32	0,126	1,6	100	328	30	1,2	4,1	9,0
120115000774	4,8	3/16	0,181	2,2	100	328	40	1,6	5,8	12,8
120115000874	5,0	1/5	0,197	2,4	100	328	45	1,8	6,2	13,6
120115001174	6,0	7/32	0,283	3,4	100	328	55	2,2	9,0	19,8
120115001274	6,3	1/4	0,310	3,8	100	328	60	2,4	10,1	22,1
120115001474	7,0	9/32	0,385	4,7	50	164	65	2,6	12,4	27,3
120115001574	8,0	5/16	0,500	6,0	50	164	75	3,0	16,1	35,3
120115001674	9,5	3/8	0,710	8,5	50	164	90	3,5	22,7	49,9
120115001774	10,0	7/16	0,785	9,4	50	164	95	3,7	25,3	55,6
120115001874	12,0	15/32	1,130	13,5	50	164	110	4,3	36,4	80,0
120115001974	12,5	1/2	1,230	14,8	50	164	115	4,5	39,4	86,6
120115002374	15,0	19/32	1,770	21,5	50	164	140	5,5	56,7	124,8
120115002574	18,0	3/4	2,540	31,0	50	164	170	6,7	81,5	179,4
120115002774	20,0	25/32	3,140	40,0	50	164	180	7,1	100,6	221,3