



The EXTRUDINGSKILL Round-Belts are made of polyurethane and are characterized by high flexibility; they can be used as a transport and transmissions belts, for example in the presence of roller conveyors. Thanks to their elasticity, the round belts can be installed on conveyors without tensioner, this allows for machines with compact design. The Round-Belts show high chemical resistance and hydrolysis resistance is higher than the polyurethanes existing standards on the market. The round straps EXTRUDINGSKILL are resistant to oils and fats.

Material: **PU**
Hardness: **SH 85 A**
Colour: **TRANSPARENT**
Tolerance: **+/- 3 SHA**

CODE	DIAMETER Ø		CROSS SECTION	APPROX WEIGHT	STANDARD ROLL		RECOMMENDED MIN. PULLEY Ø		FMAX/BELT (STANDARD)	
	MM	INCH			CM ²	KG/100M	M	FT	MM	INCH
110117101174	6,0	7/32	0,283	3,4	100	328	60	2,3	10,4	22,9
110117101574	8,0	5/16	0,500	6,0	50	164	80	3,2	18,4	40,4
110117101774	10,0	7/16	0,785	9,4	50	164	100	3,9	28,6	62,8
110117101874	12,0	15/32	1,130	13,5	50	164	120	4,7	40,8	89,8
110117102374	15,0	19/32	1,770	21,5	50	164	150	5,9	64,9	142,7
110117102574	18,0	3/4	2,540	31,0	50	164	190	7,5	92,8	204,2
110117102774	20,0	25/32	3,140	40,0	50	164	200	7,9	115,3	253,6