



The EXTRUDINGSKILL Round-Belts are made of polyurethane and are characterized by high flexibility; they can be used as a transport and transmissions belts, for example in the presence of roller conveyors. Thanks to their elasticity, the round belts can be installed on conveyors without tensioner, this allows for machines with compact design. The Round-Belts show high chemical resistance and hydrolysis resistance is higher than the polyurethanes existing standards on the market. The round straps EXTRUDINGSKILL are resistant to oils and fats.

Material: **PU**
Hardness: **SH 85 A**
Colour: **TRANSPARENT**
Tolerance: **+/- 3 SHA**

CODE	DIAMETER Ø		CROSS SECTION	APPROX WEIGHT	STANDARD ROLL		RECOMMENDED MIN. PULLEY Ø		FMAX/BELT (STANDARD)	
	MM	INCH			CM ²	KG/100m	M	FT	MM	INCH
110117501174	6,0	7/32	0,283	3,4	100	328	55	2,2	9,0	19,8
110117501574	8,0	5/16	0,500	6,0	50	164	80	3,2	16,1	35,3
110117501774	10,0	7/16	0,785	9,4	50	164	100	4,0	25,3	55,6
110117501874	12,0	15/32	1,130	13,5	50	164	110	4,4	36,4	80,0
110117502374	15,0	19/32	1,770	21,5	50	164	150	5,9	60,8	133,8
110117502574	18,0	3/4	2,830	31,0	50	164	170	6,8	91,0	200,1
110117502774	20,0	25/32	3,140	40,0	50	164	190	7,6	100,6	221,3