



The EXTRUDINGSKILL Round-Belts are made of polyurethane and are characterized by high flexibility; they can be used as a transport and transmissions belts, for example in the presence of roller conveyors. Thanks to their elasticity, the round belts can be installed on conveyors without tensioner, this allows for machines with compact design. The Round-Belts show high chemical resistance and hydrolysis resistance is higher than the polyurethanes existing standards on the market. The round straps EXTRUDINGSKILL are resistant to oils and fats.

Material: **PU**
Hardness: **SH 88 A**
Colour: **GREEN**
Tolerance: **+/- 3 SHA**

CODE	DIAMETER Ø		CROSS SECTION	APPROX WEIGHT	STANDARD ROLL		RECOMMENDED MIN. PULLEY Ø		FMAX/BELT (STANDARD)	
	MM	INCH			CM ²	KG/100M	M	FT	MM	INCH
110115000185	2,0	5/64	0,032	0,5	100	328	15	0,6	1,2	2,7
110115000285	3,0	1/8	0,071	0,9	100	328	25	1,0	2,7	5,8
110115000585	4,0	5/32	0,126	1,6	100	328	35	1,4	4,7	10,3
110115000785	4,8	3/16	0,181	2,2	100	328	45	1,8	6,7	14,8
110115000885	5,0	1/5	0,197	2,4	100	328	50	2,0	7,1	15,7
110115001185	6,0	7/32	0,283	3,4	100	328	60	2,4	10,4	22,9
110115001285	6,3	1/4	0,310	3,8	100	328	65	2,6	11,4	25,1
110115001485	7,0	9/32	0,385	4,7	50	164	70	2,8	14,1	31
110115001585	8,0	5/16	0,500	6,0	50	164	80	3,2	18,4	40,4
110115001685	9,5	3/8	0,710	8,5	50	164	95	3,8	25,9	57
110115001785	10,0	7/16	0,785	9,4	50	164	100	4,0	28,6	62,8
110115001885	12,0	15/32	1,130	13,5	50	164	120	4,8	40,8	89,8
110115001985	12,5	1/2	1,230	14,8	50	164	125	5,0	44,9	98,7
110115002385	15,0	19/32	1,770	21,5	50	164	150	6,0	64,9	142,7
110115002585	18,0	3/4	2,540	31,0	50	164	180	7,2	92,8	204,2
110115002785	20,0	25/32	3,140	40,0	50	164	220	8,8	115,3	253,6