



The EXTRUDINGSKILL Round-Belts are made of polyurethane and are characterized by high flexibility; they can be used as a transport and transmissions belts, for example in the presence of roller conveyors. Thanks to their elasticity, the round belts can be installed on conveyors without tensioner, this allows for machines with compact design. The Round-Belts show high chemical resistance and hydrolysis resistance is higher than the polyurethanes existing standards on the market. The round straps EXTRUDINGSKILL are resistant to oils and fats.

Material: **PU**
Hardness: **SH 90 A**
Colour: **RED**
Tolerance: **+/- 3 SHA**

CODE	DIAMETER Ø		CROSS SECTION	APPROX WEIGHT	STANDARD ROLL		RECOMMENDED MIN. PULLEY Ø		FMAX/BELT (STANDARD)	
	MM	INCH			CM ²	KG/100M	M	FT	MM	INCH
110115000166	2,0	5/64	0,032	0,5	100	328	20	0,8	1,9	4,1
110115000266	3,0	1/8	0,071	0,9	100	328	30	1,2	3,4	7,4
110115000566	4,0	5/32	0,126	1,6	100	328	40	1,6	5,9	12,9
110115000766	4,8	3/16	0,181	2,2	100	328	50	2,0	8,5	18,7
110115000866	5,0	1/5	0,197	2,4	100	328	55	2,2	9,3	20,4
110115001166	6,0	7/32	0,283	3,4	100	328	65	2,6	13,3	29,2
110115001266	6,3	1/4	0,310	3,8	100	328	70	2,8	14,6	32,2
110115001466	7,0	9/32	0,385	4,7	50	164	75	3,0	18,3	40,2
110115001566	8,0	5/16	0,500	6,0	50	164	85	3,4	23,8	52,3
110115001666	9,5	3/8	0,710	8,5	50	164	95	3,8	33,3	73,2
110115001766	10,0	7/16	0,785	9,4	50	164	105	4,2	37,3	82,0
110115001866	12,0	15/32	1,130	13,5	50	164	120	4,8	53,3	117,2
110115001966	12,5	1/2	1,230	14,8	50	164	125	5,0	58,0	127,6
110115002366	15,0	19/32	1,770	21,5	50	164	150	6,0	83,6	184,0
110115002566	18,0	3/4	2,540	31,0	50	164	185	7,4	119,8	263,5
110115002766	20,0	25/32	3,140	40,0	50	164	200	8,0	148,3	326,2