



EXTRUDINGSKILL produces profiles, guides, containment edges with special blend of thermoplastic PVC, PU and Special Compound in different hardness (Shore A) able to guarantee flexibility and resistance to abrasion and oils. Profiles, guides and sidewalls have been studied by EXTRUDINGSKILL to perfectly fit to hedging compounds of the conveyor belts and are applied using different vulcanization systems such as hot air and high frequency system that guarantee a perfect and long lasting bond, using equipment normally available in Italy at our Milan headquarter and at our branch of Onore (Bergamo) or in Russia at our office in Moscow.

Material: **PVC**
Hardness: **SH 60 A**
Colour: **BLUE**
Tolerance: **+/- 3 SHA**

| CODE | PROFILE DIMENSION (BXH) | APPROX WEIGHT | STANDARD ROLL | | MIN. PULLEY Ø CONV. SIDE TRANS | | MIN. PULLEY Ø CONV. SIDE LONG. | | MIN. PULLEY Ø RUNNING SIDE | |
|--------------|-------------------------|---------------|---------------|-----|--------------------------------|------|--------------------------------|------|----------------------------|------|
| | | KG/M | M | FT | MM | INCH | MM | INCH | MM | INCH |
| 431306012448 | 8X8 (S8) | 0,08 | 300 | 984 | 40 | 1,6 | 60 | 2,3 | 50 | 2,0 |
| 431306012648 | 10X10 (S10) | 0,12 | 250 | 820 | 50 | 2,0 | 80 | 3,2 | 70 | 2,8 |
| 431306005848 | 12X12 (S12) | 0,18 | 200 | 656 | 50 | 2,0 | 80 | 3,2 | 70 | 2,8 |