



The Extrudingskill Cleats cross cleats, easily weldable on PVC or PU based belts, to transport products on horizontal, vertical and inclined conveyors. They grant a perfect flexibility and resistance to abrasion and oils.

Material: **PVC FDA**
 Hardness: **SH 63 A**
 Colour: **WHITE**
 Tolerance: **+/- 3 SHA**



| CODE | TYPE | CARRIER BASE | | CARRIER HEIGHT | | CARRIER ANGLE | MIN. PITCH OF CARRIER TRANSV. | | MIN. DRUM FLEXING TRANSV. | | (SH A) |
|--------------|------|--------------|-------|----------------|---------|---------------|-------------------------------|------|---------------------------|------|--------|
| | | MM | INCH | MM | INCH | | MM | INCH | MM | INCH | |
| 54230301573D | N20 | 25 | 63/64 | 20 | 25/32 | | | | | | 63 |
| 54230300903D | N30 | 25 | 63/64 | 30 | 1 3/16 | | | | | | 63 |
| 54230301453D | N40 | 25 | 63/64 | 40 | 1 37/64 | | | | | | 63 |
| 54230301463D | N50 | 25 | 63/64 | 50 | 1 31/32 | | | | | | 63 |
| 54320301473D | N60 | 25 | 63/64 | 60 | 2 23/64 | | | | | | 63 |