



The Extrudingskill Cleats cross cleats, easily weldable on PVC or PU based belts, to transport products on horizontal, vertical and inclined conveyors. They grant a perfect flexibility and resistance to abrasion and oils.

Material: **PU FDA**
Hardness: **SH 85 - 92 A**
Colour: **BLUE**
Tolerance: **+/- 3 SHA**



| CODE | TYPE | CARRIER BASE | | CARRIER HEIGHT | | CARRIER ANGLE | MIN. PITCH OF CARRIER TRANSV. | | MIN. DRUM FLEXING TRANSV. | | (SH A) |
|--------------|------|--------------|-------|----------------|---------|---------------|-------------------------------|------|---------------------------|------|--------|
| | | MM | INCH | MM | INCH | | MM | INCH | MM | INCH | |
| 521703014844 | T20 | 13 | 33/64 | 20 | 25/32 | | | | | | 85 |
| 521703014847 | T20 | 13 | 33/64 | 20 | 25/32 | | | | | | 92 |
| 521703014944 | T30 | 13 | 33/64 | 30 | 1 3/16 | | | | | | 85 |
| 521703014947 | T30 | 13 | 33/64 | 30 | 1 3/16 | | | | | | 92 |
| 521703015044 | T40 | 13 | 33/64 | 40 | 1 37/64 | | | | | | 85 |
| 521703015047 | T40 | 13 | 33/64 | 40 | 1 37/64 | | | | | | 92 |
| 521703015144 | T50 | 13 | 33/64 | 50 | 1 31/32 | | | | | | 85 |
| 521703015147 | T50 | 13 | 33/64 | 50 | 1 31/32 | | | | | | 92 |
| 521703015244 | T60 | 13 | 33/64 | 60 | 2 23/64 | | | | | | 85 |
| 521703015247 | T60 | 13 | 33/64 | 60 | 2 23/64 | | | | | | 92 |